

Connectors / Anschlüsse

QuickClip4

391825, 391693, 600287, 600288 • DE/EN • 04/2021

Waterproof and simple parallel connector for solar modules with standard connectors. QuickClip4 are compatible with commercially available 4 mm PV connectors (Standard4).

Wasserdichter und einfacher Parallelverbinder für Solarmodule mit Standard-Steckern. QuickClip4 sind kompatibel mit handelsüblichen 4 mm PV-Steckverbindern (Standard4).



Technical Data	Technische Daten		QuickClip4 Set 2in1, short	QuickClip4 Set 2in1, long	QuickClip4 Set 3in1	QuickClip4 Set 4in1
Rated voltage	Nennspannung	VDC	1000			
Rated current	Nennstrom	A	30			
Rated impulse voltage	Nennstoßspannung	V	8000	-	-	-
Contact resistance	Kontaktwiderstand		≤0,5m Ω			
Ambient temperature	Umgebungstemperatur	°C	-40 - +90	-40 - +85	-40 - +85	-40 - +85
Degree of protection	Schutzgrad		IP67	IP65	IP67	IP67
Insertion force	Einsteckkraft	N	≤50	≤60	≤50	≤50
Withdrawal force	Aussteckkraft	N	≤50	≤60	≤50	≤50
Contact material	Kontaktmaterial		Silver plated copper Versilbertes Kupfer			
Insulation material	Isoliermaterial		PPO			
Dimension	Abmessung	LxWxH LxBxH	109x82x15 mm	290x60x15 mm	330x60x40 mm	510x80x40 mm
Weight	Gewicht	kg	0,12	0,12	0,20	0,40
Article number	Artikelnummer		391825	391693	600287	600288