replink Reolink Innovation Limited					
Picture	THE STATE OF THE S				
Model	Lumus Series E430				
	Image Sensor	1/2.7" CMOS			
	Resolution	2560 x 1440 (4 MP)@15FPS			
	Lens	f=2.8mm, Max: F2			
	Video Compression	H.264			
	Field of View	Horizontal:107°			
		Vertical: 57°			
Video & Audio	Infrared Night Vision	Up to10m (33ft) (LED: 6pcs/0.8W/850nm) (Auto-switching with IR-cut filter)			
	Color Night Vision	With spotlights: 1.6W/6500K/180Im			
	Frame Rate	Main stream: 2fps - 15fps (default: 15fps)			
		Sub stream: 4fps - 15fps (default: 10fps)			
	Code Rate	Main stream: 1024Kbps - 3072Kbps (default: 3072Kbps)			
		Sub stream: 64Kbps - 512Kbps (default: 256Kbps)			
	Audio	Two-way audio			
Power Requirements	DC Power	DC 5.0V/1A, <6W			
	Power Port	DC power port			
Interface	SD Card Slot	Supports Max. 256GB microSD card			
	Reset Button	YES			
	Audio In/Out	Built-in microphone and speaker			
Wi-Fi	Wireless Standard	IEEE 802.11a/ b/g/n			
	Operating Frequency	2.4GHz/5GHz			
	Wireless Security	WPA/WPA2			
	OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android			
	Protocols & Standards	SSL, TCP/IP, IPv4, UPnP, SMTP, NTP, DHCP, DNS, DDNS, P2P			
	User Access	Max. 20 users (1 admin & 19 user); Max. 12 simultaneous streams (2 main & 10 sub streams)			
	Smart Alarm	Motion detection; person detection; vehicle detection; animal detection			

Other Features	Recording Modes	Motion-triggered recording (default); Scheduled recording, 24/7 recording		
	Time Lapse	YES		
	Smart Home Compatibility	Google Assistant		
Working Environment	Operating Temperature	-10°C~+55°C (14°F~131°F)		
	Operating Humidity	10% ~ 90%		
	Weatherproof	IP65		
Mechanical	Dimensions	99 x 91 x 60mm		
	Weight (Battery Included)	168g		
Warranty	Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/.		