

EOS M200

EINFACH UNGLAUBLICH, UNGLAUBLICH EINFACH

Überwinde die Grenzen deines Smartphones. Mit dieser intuitiv bedienbaren EOS Kamera, mit der du ganz einfach professionell wirkende Aufnahmen machst kannst du deine Erinnerungen auf eine neue Art erleben. Wechsle die Objektive und halte die Stimmung jeder Situation im Bild fest - auch bei wenig Licht.



- **24.1 Megapixel APS-C Sensor**
Begeisterung pur: unglaubliche Details und beeindruckende Farben
- **4K Video und HD-Videos mit bis zu 120B/s**
Detailreiche Aufnahmen, auch in Zeitlupe
- **Dual Pixel CMOS AF**
Schnell für Fotos, gleichmäßig bei Video - auch bei wenig Licht bis -4EV
- **Kompakt und leicht**
Die besonderen Momente des Lebens ganz einfach mit der Kamera festhalten – so wie sie es verdienen
- **Kreativ-Assistent**
Ganz einfach professionell aussehende Fotos aufnehmen
- **Bluetooth und WLAN**
Zum Fernsteuern der Kamera und Teilen der Aufnahmen
- **180° klappbares Touchscreen-LCD**
Für kreative Bilder und Selfies
- **Zeitraffer-Movies**
Bewegungen in anderen Zeitdimensionen aufzeichnen

24.1 MEGA
PIXELS
CMOS

EOS Movie
4K+FULL HD

Dual Pixel AF
CMOS

Wi-Fi
Bluetooth®

Tilt-up LCD
180°

4K
4K Time-Lapse
Movie

PRODUKT RANGE

EOS M6 Mark II
EOS M50
EOS M200



EOS M6 Mark II



EOS M50



EOS M200

Canon

Live for the story_

TECHNISCHE DATEN

EOS M200

IMAGE SENSOR		SHUTTER	
Type	22.3 x 14.9mm CMOS	Type	Vertical-travel mechanical focal-plane shutter, electronically controlled at all speeds
Effective Pixels	Approx. 24.1 megapixels	Speed	30 - 1/4000 sec (1/3 stop increments), Bulb (Total shutter speed range. Available range varies by shooting mode)
Total Pixels	Approx 25.8 megapixels		
Aspect Ratio	3:2		
Low-Pass Filter	Built-in/Fixed	WHITE BALANCE	
Sensor Cleaning	EOS integrated cleaning system	Type	Auto white balance with the imaging sensor
Colour Filter Type	Primary Colour	Settings	Auto (Ambience Priority), Auto (White Priority), Daylight, Shade, Cloudy, Tungsten light, White Fluorescent light, Flash, Custom, Colour Temperature (100 Kelvin increments)
IMAGE PROCESSOR			
Type	DIGIC 8	Custom White Balance	White balance compensation: 1. Blue/Amber +/-9 levels 2. Magenta/ Green +/-9 levels Yes, 1 setting can be registered
LENS		VIEWFINDER	
Lens Mount	EF-M (EF and EF-S lenses compatible via Mount adapter EF-EOS M)	LCD MONITOR	
Focal Length	Equivalent to 1.6x the focal length of the lens	Type	7.5 cm (3.0") Touchscreen LCD (TFT). 3:2 aspect ratio. Approx. 1,040,000 dots. Electrostatic capacitive type. Tilting approx 180° upward
Image Stabilisation	Optical Image Stabilizer on compatible lens	Coverage	Approx 100%
	Movie: In-camera Digital IS available. Further stabilisation enhancements from lenses compatible with Dynamic IS	Viewing Angle (horizontally/vertically)	Approx 170° horizontally and vertically
FOCUSING		Brightness Adjustment	Adjustable to one of seven levels
Type	Dual Pixel CMOS AF System. Phase detection pixels built onto imaging sensor ^[20]	Display Options	Customisable and toggle via INFO. Button (1) Liveview image with exposure info (2) Liveview image with basic info (3) Liveview image with full info
	Contrast detection method is used during 4K Movie and 4K Timelapse Movie		
AF System/ Points	Maximum 143 points depending on lens. Max 25 frames in Zone AF ^[15]	FLASH	
	Freely position 1 AF point/ 1 AF Zone via manual selection (area available lens dependent)	Built-in Flash GN (ISO 100, meters)	5
AF working range	EV -4 - 18 (room temperature, f/1.4, ISO 100, One-Shot AF), Movie: EV -2 - 18 (room temperature, f/1.4, ISO 100, One-Shot AF, 29.97fps/25fps)	Built-in Flash Coverage	Maximum coverage at approx. 15mm (35mm equivalent: approx. 24mm) Approx. 4 seconds ^[27]
AF Modes	One-Shot AF and Servo AF	Built-in Flash recycle time	Auto (E-TTL II)
AF Point Selection	Face + Tracking (Eye Detection AF available)	Modes	Provided
	Zone AF	Red-Eye Reduction	1/200sec
	1-point AF	X-sync	+/- 2 EV in 1/3 increments
Selected AF point display	Spot AF	Flash Exposure Compensation	Yes
AF Lock	Indicated on LCD monitor	Flash Exposure Lock	Yes
	Locked when shutter button is pressed half way or AE Lock Button	Second Curtain Synchronisation	No/No
AF Assist Beam	via LED assist beam	HotShoe/ PC terminal	none
Manual Focus	With EF & EF-S lenses - Select via AF/MF switch on lens With EF-M lenses - Select via menu MF Peaking available AF+MF available (Manual focus adjustment after One-Shot AF) Magnify image available during MF (5x or 10x)	External Flash Compatibility	
Focus Bracketing		SHOOTING	
AF Micro adjustment		Modes	Scene Intelligent Auto, Hybrid Auto, Creative Assist, SCN(Self-Portrait, Portrait, Smooth Skin, Landscape, Sports, Close-up, Food, Night Portrait, Handheld Night Scene, HDR Backlight Control), Creative Filters (Grainy B/W, Soft Focus, Fish-eye Effect, Water painting effect, Toy camera effect, Miniature effect, HDR Art standard, vivid, bold, embossed), Program AE, Shutter priority AE, Aperture priority AE, Manual exposure, Movie (Movie auto exposure, Manual manual exposure, Time-lapse movie)
EXPOSURE CONTROL		Picture Styles	Auto, Standard, Portrait, Landscape, Fine Detail, Neutral, Faithful, Monochrome, User Defined (x3)
Metering modes	Real-time metering from the image sensor (1) Evaluative metering (384 zones) (2) Partial metering at center (approx. 5.8% of Live View Screen) (3) Center weighted average metering (4) Spot metering (approx. 2.9% of Live View Screen)	Colour Space	sRGB and Adobe RGB
Metering Range	Still image: EV -1 - 20 (at 23 °C, ISO 100) Movie: EV 0 - 20 (at 23 °C, ISO 100)		
AE Lock	Auto: In One-shot AF mode with evaluative metering exposure is locked when focus is achieved. Manual: By AE lock Button in creative zone modes. +/-3 EV in 1/3 stop increments		
Exposure Compensation			
AEB			
ISO Sensitivity⁽⁸⁾	100 - 25600 in 1/3 stop increments. Max in Auto can be set from 400 - 25600 4K Movie: 100 - 6400 in 1/3-stop increments. Full HD and HD Movie: ISO 100 - 12800 in 1/3-stop increments. ISO can be expanded to 25600		

Canon

Live for the story_

TECHNISCHE DATEN

EOS M200

Image Processing	Highlight Tone Priority (standard and enhanced) Auto Lighting Optimizer (4 settings) Long exposure noise reduction High ISO speed noise reduction (4 settings + Multi Shot NR) Lens peripheral illumination correction Chromatic aberration correction Diffraction correction Digital Lens Optimizer	OTHER FEATURES	
Drive modes	Creative Assist: Presets Background Blur (5 settings) Brightness (19 levels) Contrast (9 levels) Saturation (9 levels) Color Tone 1 & 2 (19 levels) Monochrome (Off/Black and white/Sepia/Blue/Purple/Green)	Custom Functions	6 custom functions
Continuous Shooting	Single, Continuous, Self timer (2s, 10s, Continuous) One shot AF: Approx. 6.1 shots/sec ^[21] With Servo AF: Approx. 4 shots/sec ^[22]	Metadata Tag	User copyright information (Author's Name, Copyright Details) Image rating (0-5 stars)
LIVE VIEW MODE		Playback zoom	15 steps plus smooth pinch-to-zoom
Coverage	Approx. 100% (horizontally and vertically)	Display Formats	(1) Single image with information (toggle options) (2) Single image (3) Index display (4/9/36/100 images) (4) Jump Display (1/10/custom number image, by shot date, by rating, by folder, by movies only, protected only) Playback time: 1/2/3/5/10/30 seconds Repeat: On/Off Transition Effects: Off, Slide in 1-2, Fade 1-3 Brightness/ RGB
FILE TYPE		Slide Show	Yes
Still Image Type	JPEG: Fine, Normal (Exif 2.31 compliant) / Design rule for Camera File system (2.0) RAW: RAW (CR3 14-bit), Digital Print Order Format [DPOF] Version 1.1 compliant	Histogram	Erase: Single image, Selected images, Selected range, All images
RAW+JPEG simultaneous recording	Yes, RAW + various JPEG compression possible	Highlight Alert	Protection: Selected images, Selected range, All images. Unprotect all images
Image Size	RAW: (3:2) 6000 x 4000, (4:3) 5328 x 4000, (16:9) 6000 x 3368, (1:1) 4000 x 4000 JPEG 3:2: (L) 6000 x 4000, (M) 3984 x 2656, (S1) 2976 x 1984, (S2) 2400 x 1600 JPEG 4:3: (L) 5328 x 4000, (M) 3552 x 2664, (S1) 2656 x 1992, (S2) 2112 x 1600 JPEG 16:9: (L) 6000 x 3368, (M) 3984 x 2240, (S1) 2976 x 1680 (S2) 2400 x 1344 JPEG 1:1: (L) 4000 x 4000, (M) 2656 x 2656, (S1) 1984 x 1984, (S2) 1600 x 1600	Image Erase/Protection	(1) Shooting menu (x8) (2) Playback menu (x4) (3) Connectivity menu (x2) (4) Setup menu (x5) (5) Display menu (6) My Menu 29 Languages English, German, French, Dutch, Danish, Portuguese, Finnish, Italian, Norwegian, Swedish, Spanish, Greek, Russian, Polish, Czech, Hungarian, Romanian, Ukrainian, Turkish, Arabic, Thai, Simplified Chinese, Traditional Chinese, Korean, Malay, Vietnamese, Indonesian, Hindi, Japanese
Movie Type	In-camera RAW processing & Image Resize available in playback MP4 [Video: MPEG-4 AVC/H.264, Audio: MPEG-4 AAC]	Menu Categories	Firmware update possible by the user.
Movie Size	4K - 3840 x 2160 (23.98, 25 fps) Full HD - 1920 x 1080 (59.94, 50, 29.97, 25fps) HD - 1280 x 720 (119.9, 100, 59.94, 50 fps) Max duration 29min 59sec, Max file size 4GB	Menu Languages	Hi-Speed USB (Micro USB) Wireless LAN (IEEE802.11b/g/n), (2.4 GHz only, 1-11 ch), ^[17]
Movie Length		Firmware Update	Bluetooth® (Specification version 4.1, Bluetooth low energy technology) ^{[23] [25]}
Sound Files		INTERFACE	HDMI (Micro - Type-D connector)
Folders	New folders can be created and selected	Computer	
File Numbering	(1) Continuous, Auto Reset (2) Manual Reset	Other	
		DIRECT PRINT	
		Canon Printers	Canon Compact Photo Printers and PIXMA Printers supporting PictBridge
		PictBridge	Canon Compact Photo Printers and PIXMA Printers supporting PictBridge
		STORAGE Type	SD, SDHC, SDXC (UHS-I compatible)



TECHNISCHE DATEN

EOS M200

SUPPORTED OPERATING SYSTEM		All data is based on Canon standard testing methods except where indicated. Subject to change without notice.
PC & Macintosh	For individual software see service and support sections	^[5] Based on the CIPA Standard and using the batteries and memory card format supplied with the camera, except where indicated
SOFTWARE		^[6] Recommended Exposure Index
Browsing & Printing	Digital Photo Professional, DPP Express for iPad	^[15] Maximum number of AF frame is dependent on selected image aspect ratio
Image Processing	Picture Style Editor, EOS Utility, Image Transfer Utility 2	^[17] Wi-Fi use may be restricted in certain countries or regions.
Other	Camera Connect app available on iOS and Android devices ^[25]	^[20] Dual Pixel CMOS AF - AF is possible over an area of approx. 80% Vertical x 80% Horizontal of the frame
POWER SOURCE		^[21] Continuous shooting speed is measured with EF-M 15-45mm f/3.5-6.3 IS STM and requires SDHC/SDXC UHS Speed Class 1 memory card. Total number of frames captured and continuous shooting speed may vary depending on camera exposure settings, type of lens used, battery level, light level and memory card used.
Batteries	1 x Rechargeable Li-ion Battery LP-E12	^[22] Continuous shooting speed is measured with EF-M 15-45mm f/3.5-6.3 IS STM and requires SDHC/SDXC UHS Speed Class 1 memory card. Under Servo AF, maximum continuous shooting speed and total number of frames captured depends on subject condition, camera settings and lens used
Battery life	Approx. 315 shots (conforms to CIPA) ^[5] Eco Mode: Approx. 485 shots Movie Recording: Approx. 90 mins Playback time when playing back a slideshow of still images: Approx. 4 hrs 55mins 4 levels	^[23] Equipped with Bluetooth® low energy technology. The Bluetooth® word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. and any use of such marks by Canon Europe Ltd. is under license. Other trademarks and trade names are those of their respective owners.
Battery Indicator	Display off (15, 30 sec or 1, 3, 5, 10, 30 mins)	^[25] Bluetooth functionality with Camera Connect app requires smart device to be equipped with Bluetooth version 4.0 (or later). Also requires smart device to be using operating system iOS 8.4 (or later) or Android 5.0 (or later)
Power saving	Auto Power Down (30 sec or 1, 3, 5, 10 mins, Disable) ECO mode	^[27] When battery is fully charged
Power Supply & Battery Chargers	Battery charger LC-E12 Compact Power Adapter CA-PS700 DC Coupler DR-E12	
PHYSICAL SPECIFICATIONS		
Body Materials	Polycarbonate	
Operating Environment	0 – 40 °C, 85% or less humidity	
Dimensions (WxHxD)	108.2 x 67.1 x 35.1mm	
Weight (body only)	Approx 299g (black), 299g (white), CIPA testing standard including battery and memory card	
ACCESSORIES		
Cases / Straps	EM-200DB EM-E2	
Lenses	EF-M lenses All EF and EF-S lenses compatible via Mount adapter EF-EOS M	
Remote Controller/ Switch	Bluetooth Remote BR-E1	
Other	Interface cable IFC-600PCU Mount Adapter EF-EOSM	



Live for the story_

Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
Canon Europa NV 2019

EINFACH UNGLAUBLICH, UNGLAUBLICHEINFACH

EOS M200

Überwinde die Grenzen deines Smartphones. Mit dieser intuitiv bedienbaren EOS Kamera, mit der du ganz einfach professionell wirkende Aufnahmen machst kannst du deine Erinnerungen auf eine neue Art erleben. Wechsle die Objektive und halte die Stimmung jeder Situation im Bild fest - auch bei wenig Licht.

Verkaufsstart: Oktober 2019



DETAILS ZUM PRODUKT:

Produktname	Mercury Code	EAN Code
Digitalkamera EOS M200 BK M15-45 EU26	3699C010AA	4549292142280
Digitalkamera EOS M200 WH M15-45 SEU26	3700C010AA	4549292142297
Digitalkamera EOS M200 BK M15-45+M55-200 EU26	3699C018AA	4549292142976

OPTIONAL ERHÄLTliches ZUBEHÖR:

Zubehörbezeichnung	Mercury-Code	EAN Code
Stromversorgung		
Akkuladegerät LC-E12E	6782B004AA	8714574626291
Akku LP-E12	6760B002AA	4960999911625
Netzadapter CA-PS700	7875A003AA	4960999112237
Gleichstromkupppler DR-E12	6785B001AA	4960999913278
Kabel		
USB-Kabel IFC-600U	1015C001AA	4549292054378
Sonstiges		
EF-EOS M Adapter	6098B005AA	4960999841137
EF-EOS M Adapter (ohne Stativanschluss)	0135T435	N/A
Fernsteuerung		
Kabellose Fernbedienung BR-E1	2140C001AA	4549292087864
Camera Connect App	N/A	N/A
Schulter- und Tragegurte		
Umhängegurt Schwarz EM-E2 (BK)	1661C001AA	4549292078596
NUmhängegurt Braun EM-E2 (BW)	9930B001AA	4549292021257
Umhängegurt EM-200DB	9929B001AA	4549292021271
Canon Face Jacket EH31-FJ (Light Brown)	2261C001AA	4549292097153
Canon Face Jacket EH31-FJ(DB)	2262C001AA	4549292097184
Canon Face Jacket EH31-FJ(Yellow)	2263C001AA	4549292097207
Canon Face Jacket EH31-FJ(Navy)	2265C001AA	4549292097245
Canon Face Jacket EH31-FJ(Red)	2266C001AA	4549292100587
Canon Face Jacket EH31-FJ (Border blue)	2268C001AA	4549292097283

Canon

Live for the story_

EINFACH UNGLAUBLICH, UNGLAUBLICHEINFACH

EOS M200

Überwinde die Grenzen deines Smartphones. Mit dieser intuitiv bedienbaren EOS Kamera, mit der du ganz einfach professionell wirkende Aufnahmen machst kannst du deine Erinnerungen auf eine neue Art erleben. Wechsle die Objektive und halte die Stimmung jeder Situation im Bild fest - auch bei wenig Licht.

Verkaufsstart: Oktober 2019



ABMESSUNGEN / LOGISTIKINFORMATIONEN:

Produktname	Mercury Code	Packart	Paketbeschreibung	Menge	Länge (ca. cm)	Breite (ca. cm)	Höhe (ca. cm)	Bruttogewicht (ca. kg)
Digitalkamera EOS M200 BK M15-45	3699C010AA	EA	Einzel	1	16,8	16,8	13,8	0,926
		CT	Karton	6	43,5	35,8	20,55	6,28
		EP	Europalette	150	120	80	118	167
			Lagen pro Palette	5				
			Kartons pro Lage	5				
			Produkte pro Lage	30				
Digitalkamera EOS M200 WH M15-45 SL	3700C010AA	EA	Einzel	1	16,8	16,8	13,8	0,921
		CT	Karton	6	43,5	35,8	20,55	6,28
		EP	Europalette	150	120	80	118	167
			Lagen pro Palette	5				
			Kartons pro Lage	5				
			Produkte pro Lage	30				
Digitalkamera EOS M200 BK M15-45+M55-200	3699C018AA	EA	Einzel	1	22,4	16,8	13,8	1,212
		CT	Karton	6	43,5	35,8	25,2	8,03
		EP	Europalette	120	120	80	115,8	171
			Lagen pro Palette	4				
			Kartons pro Lage	5				
			Produkte pro Lage	30				

Lieferumfang

EOS M200 BK M15-45

- Digitalkamera EOS M200 Gehäuse Schwarz
- Kamera-Gehäusedeckel R-F-4
- Tragegurt EM-200DB
- Akku LP-E12
- Akkuladegerät LC-E12E
- Netzkabel
- Anleitungen
- EF-M 15-45mm f/3.5-6.3 IS STM
- Objektivdeckel E-49
- Objektivrückdeckel EB

EOS M200 WH M15-45

- Digitalkamera EOS M200 Gehäuse Weiß
- Kamera-Gehäusedeckel R-F-4
- Tragegurt EM-200DB
- Akku LP-E12
- Akkuladegerät LC-E12E
- Netzkabel
- Anleitungen
- EF-M 15-45mm f/3.5-6.3 IS STM
- Objektivdeckel E-49
- Objektivrückdeckel EB

EOS M200 BK M15-45+M55-200

- Digitalkamera EOS M200 Gehäuse Schwarz
- Kamera-Gehäusedeckel R-F-4
- Tragegurt EM-200DB
- Akku LP-E12
- Akkuladegerät LC-E12E
- Netzkabel
- Anleitungen
- EF-M 15-45mm f/3.5-6.3 IS STM
- Objektivdeckel E-49
- Objektivrückdeckel EB EF-M55-200mm f/4.5-6.3 IS STM
- Objektivdeckel E-52 II
- Objektivrückdeckel EB

